



BARRIER-FREE VERSACOOLER II P8AC, PAC

Suggested Specification

Model P8AC shall deliver 8.0 gph of 50° F degree water at 90° F ambient and 80° F inlet water. Model PAC is a non-refrigerated drinking fountain and delivers ambient water. Models P8AC and PAC shall include front and side mechanical push pads to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Bubbler shall be one piece with flexible guard and operate between 20 and 120 PSI. Cabinet finish shall be Sandstone or Greystone powder coated paint on galvanized steel or brushed Stainless Steel. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards. Shall comply with ANSI/NSF 61.

Models

P8AC delivers 8.0 gallons of chilled drinking water per hour.

PAC is a non-refrigerated fountain.

Standard Features

- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways Are Lead-Free In Materials & Construction
- > Stainless Steel Top Flexible Bubbler Guard
- > Heavy Duty Galvanized Steel Frame
- > High Efficiency Cooling Tank and Coil
- > Refrigerant R-134a
- > Four Push Pad Activation
- > External Stream Height Adjustment> Mechanical Activation

Finishes

- > Standard Cabinet Finish: Sandstone powder coated paint on galvanized steel
- > Optional finishes (at additional cost): Stainless Steel, Regency Bronze, and optional powder coated finishes

Installation

- > Prior to roughing consult with local, state, and federal codes for proper mounting height.
- > Shipped with complete instructions and wall mounting bracket.
- > Removable side and front panels provide easy access for installation

Options (at additional cost)

- ☐ Glass Fillers (Factory Installed)
- ☐ Push Handle (029603-004)
- ☐ Push Back (029603-005)
- ☐ Push Down (029603-006)
- ☐ One piece Chrome Plated Brass Bubbler (036700-001)

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty: One year on component parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request

These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed.

This product is certified to be Lead Free as defined by the Safe Drinking Water Act.

Oasis International Electric Water Coolers are listed by Underwriters laboratories Inc. and comply with both U.S. and Canadian requirements

This unit complies with ARI Standard 1010 Testing, Operating and Rating requirements (electric water coolers only).

Product Certified to NSF/ANSI Standard 61, Annex G and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953) weighted average lead content <=0.25%.

These units comply with A.R.I. Standard 1010



Oasis International Product
Certified by NSF to
NSF/ANSI Standard 61, G

Model	50° F Drinking Water 90° F Ambient Air Temp*			Hot 'N Cold™ Model	115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
P8AC**	8.0	8.0	No	No	1/4	4.6	460	Yes	Yes	59 Lbs.
PAC	Fountain Only							Yes	Yes	25 Lbs.

*Industry Standard Rating Condition 80° F inlet water temperature.

**Special export models available, operable on 220-240 volts, 50/60 Hz.

Specifications subject to change without notice

OASIS™ BARRIER-FREE Versacooler® II MODELS P8AC, PAC, P8ACEE, PF8AC, PFAC, PF8ACEE, PV8AC

