

AQUA POINTE SYSTEMS

P10BFY, PBFY

Suggested specification model P10BFY shall deliver 38 LPH of 10°C water at 32°C ambient air and 27°C inlet water. Model PBFY is a non- refrigerated bottle filler which shall deliver ambient water. Key Aqua Pointe bottle filler model components contain Freshield, which utilises a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discoloration, odors and degradation. Basin shall be designed to eliminate splashing and standing water. Cooling system shall use R-134a refrigerant.

Standard Features

- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways are Lead-free in Materials & Construction
- > Heavy Duty steel frame
- > High Efficiency cooling tank and coil> Refrigerant R-134a
- > Oasis Green Filtration System

Finishes


- > Standard cabinet finish: Brushed Stainless Steel

Options (at additional cost)

- > Oasis Non-Structural wall Mounting Bracket
- > Oasis Floor-Mounting Pedestal & Apron Kit

Installation

- > Prior to roughing, consult with local, state and federal codes for proper mounting height
- > Shipped with complete instructions & wall mounting bracket
- > Removable door panel to allow for easy access to filtration
- > Electricity, water supply and waste drainage required



This product has been tested & certified by Wras on complying with the requirements of the United Kingdom (Water Fitting) regulations / Scottish bye laws

This product has been independantly tested & certified as meeting the requirements of the LVD directive (2006/95/EC), EMC directive (2004/108/EC), RoHS Directive (2002/95/EC, 2005/618/EC) & Plastic materials in contact with foodstuff directive (2002/72/EC, 2004/1/EC 2004/19/EC, 2005/79/EC, 2007/19/EC, 2008/39/EC REGULATION 1935/2004 REGULATION 975/2009, 2006/95/EC Low Voltage Directive, 2004/108/EC Electromagnetic Compatibility Directive, 2002/95/EC, 2005/618/EC, RoHS Directive)



Freshield



Model	10° C Drinking Water 32° C Ambient Air Temp*		230 Volts, 50 HZ			Refrigerated	Net Wt. Approx.
	Rated Capacity LPH	Base Rate LPH	Compr. HP	Full Load Amps	Rated Watts		
P10BFY	38.0	38.0	1/20	2.0	320	Yes	36 kg
PBFY	–	–	–	0.02	4	No	22 Kg

*Industry Standard Rating Condition 27°C inlet water temperature.

Specifications subject to change without notice